



CYLINDER OIL (船用气缸油)

Oil Company 油公司	Specification 规格	Density 15°C 密度	Flash Pt 闪点°C	Pour Pt 凝点°C	Kinematic Viscosity 40°C 运动粘度(cst)	Kinematic Viscosity 100°C 运动粘度(cst)	Viscosity Index 粘度指数	Total Base No. mgKOH/g 总碱值
AP Oil 环球	AP CYCLINDO MC 40(SAE 40)	910	240	-12	145	14.6	96	40
	AP CYCLINDO MC 40(SAE 50)	915	250	-12	210	19.0	96	40
	AP CYCLINDO MC 70(SAE 50)	935	240	-9	200	19.0	98	70
	AP CYCLINDO MC 70(SAE 60)	940	250	-9	280	23.0	98	70
	AP CYCLINDO MC 80(SAE 50)	940	245	-9	200	19.0	98	80
CASTROL 嘉实多	CASTROL CYL TECH 40SX (SAE 50)	915	240	-9	212	19.0	100	40
	CASTROL CYL TECH 80AW (SAE 50)	945	240	-9	209	19.0	102	80
	CASTROL CYL TECH 70(SAE 50)	940	240	-12	217	19.0	98	70
BP 英国石油	ENERGOL CL050M (SAE 50)	940	240	-9	209	19.5	106	70
	ENERGOL CL 404 (SAE 40)	940	230	-9	153	13.9	90	40
MOBIL 美孚	MOBILGARD 570 (SAE 50)	935	256	-9	229	21.0	104	70
	MOBILGARD L540(SAE 50)	915	264	-6	236	21.0	105	40
EXXON 埃克森	EXXMAR X60 (SAE 50)	930	234	-9	240	19.5	94	60
	EXXMAR X70 (SAE 50)	940	230	-9	240	19.5	94	70
SHELL 壳牌	ALEXIA OIL 50 (SAE 50)	930	240	-6	200	19.5	110	70
CHEVRON 雪弗龙	TARO SPECIAL 70 (SAE 50)	930	240	-15	225	19.0	95	70
	TARO HEAVY 85 (SAE 60)	940	250	-15	320	25.0	95	85
	TARO SPECIAL 50 (SAE 50)	930	240	-15	225	19.0	95	50
	TARO HEAVY 70 (SAE 60)	940	250	-15	320	25.0	95	70
TOTAL 道达尔	TALUSIA L S40 (SAE 50)	915	220	-9	200	20.0	98	40
	TALUSIA HR 70 (SAE 50)	935	220	-9	200	20.0	98	70
	TALUSIA HR 80 (SAE 50)	940	220	-9	200	20.0	98	80
中国石油 昆仑	DCA5040 (SAE 50)	940	240	-10	240	19.0	95	40
	DCA5070 (SAE 50)	940	240	-10	245	19.5	100	70
FEOSO 东方	FEOCY OIL 54 (SAE 50)	922	240	-15	202	18.2	99	40
	FEOCY OIL 57 (SAE 50)	944	240	-15	199	19.0	100	70

Remarks: Above data are typical specifications for reference only. The content is subject to update without notice.

