



SYSTEM OIL (船用系统油)

Oil Company 油公司	Specification 规格	Density 15°C 密度	Flash Pt 闪点°C	Pour Pt 凝点°C	Kinematic Viscosity 40°C 运动粘度(cst)	Kinematic Viscosity 100°C 运动粘度(cst)	Viscosity Index 粘度指数	Total Base No. mgKOH/g 总碱值
AP Oil 环球	AP MARINO T6 (SAE 30)	890	235	-12	100	11.3	96	6
	AP MARINO T6 (SAE 40)	895	240	-12	148	14.5	96	6
	AP MARINO T8 (SAE 30)	895	235	-12	105	11.5	98	8
	AP MARINO T8 (SAE 40)	900	240	-12	143	14.4	98	8
	AP MARINO T12 30 S (SAE30)	895	230	-12	100	11.3	96	12
	AP MARINO T12 40 S (SAE40)	900	230	-12	145	14.4	96	12
CASTROL 嘉实多	CASTROL CDX30 (SAE 30)	885	226	-12	105	11.5	96	5
BP 英国石油	ENERGOL OE-HT30 (SAE 30)	900	230	-9	112	11.5	93	6
	ENERGOL DL-MP30 (SAE 30)	908	224	-9	114	11.5	93	9
	ENERGOL DL-HT40 (SAE 40)	912	230	-9	152	14.0	90	9
MOBIL 美孚	MOBILGARD 300 (SAE 30)	885	266	-12	111	12.0	97	5
EXXON 埃克森	EXXMAR XA (SAE 30)	894	262	-12	110	12.0	98	6
SHELL 壳牌	MELINA 40	885	229	-9	139	14.4	102	8
	MELINA S 30	885	227	-18	104	11.8	102	5
CHEVRON 雪弗龙	VERITAS 800 MARINE 20	890	240	-12	67.6	8.68	100	5
	VERITAS 800 MARINE 30	890	240	-12	114	12.0	94	5
	VERITAS 800 MARINE 40	900	240	-12	149	14.4	94	5
TOTAL 道达尔	ATLANTA MARINE D3005 (SAE30)	895	240	-6	105	11.5	93	5
	ATLANTA MARINE D4005 (SAE40)	900	250	-6	145	14.7	95	5
中国石油 昆仑	DCC3008 (SAE 30)	885	220	-15	125	11.7	90	8
	DCC4004 (SAE 40)	890	220	-13	152	14.5	90	4
	DCC4008 (SAE 40)	890	220	-10	149	13.1	90	8
FEOSO 东方	FEOGOD 30 (SAE 30)	890	220	-15	109	11.8	96	8
	FEOGOD 40 (SAE 40)	893	220	-10	143	14.2	96	8
	FEOMAR 30 (SAE 30)	892	220	-15	115	12.0	94	12
	FEOMAR 40 (SAE 40)	898	220	-10	146	14.1	94	12

Remarks: Above data are typical specifications for reference only. The content is subject to update without notice.

